



R K PETROLEUMS

Where Quality Comes First



GREASE

CONTENTS:

ARKO MULTI PURPOSE GREASE 2,3

3



ARKO MULTI PURPOSE GREASE 2,3

Applications :

ARKO MP greases are lithium soap based high performance greases containing highly refined base oils and rust and oxidation inhibitors which make them suitable for a wide range of automotive and industrial applications. They are recommended for anti-friction and plain bearing operating under moderate temperature and service conditions. Also recommended for use in textile mills, process industry, heavy engineering, steel plants, chemical plant and all types of wheel bearings used in automobiles.

Specifications

ARKO MP greases conform to performance standards of IS:7623: 1993 (REAFFIRMED 2001), IPSS 1-09-006-97 and US STEEL 374.

Advantages

ARKO MP Greases blend includes a lithium soap thickener which ensures good mechanical stability, resistance to water wash-out, excellent oxidation stability and protection against rust and corrosion.

Typical Specifications

Sr. No.	Characteristics	NLGI grade	
		2	3
1	Appearance / Structure	Smooth and tacky	Smooth and tacky
2	Soap type	Lithium	Lithium
3	Colour	Light yellow	Light yellow
4	Base oil type	Mineral	Mineral
5	Worked penetration at 25°C, after 60 / 60 strokes, ASTM D 217	270 – 290	230 – 250
6	Drop point, °C, ASTM D 2265, min.	190	190
7	Rust test, ASTM D 1743	passes	passes
8	Copper strip corrosion, ASTM D 4048	1a	1a

PACKING: 18kgs, 180kgs

Disclaimer: R K PETROLEUMS makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products.

Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.

Storage: All packages should be stored under cover. Avoid direct sun light or heat. Keep the container in closed / properly sealed condition to avoid contamination.

Handling, Health & safety: As with all the products, please take care to avoid environmental contamination when disposing of this product. Do not dispose the used oil to soil, drains and water. Avoid contact with skin and eyes. After skin contact wash with soap and water. This product should not cause any health problems when used in the applications suggested and the guidance provided in the safety data sheet (SDS) is followed.



R K PETROLEUMS

Where Quality Comes First

MANUFACTURERS OF:-

- ❖ HYDRAULIC OILS
- ❖ CUTTING OILS
- ❖ MACHINE OILS
- ❖ SILICONE EMULSION
- ❖ GREASES
- ❖ GEAR OILS

TRADERS & MARKETERS OF:-

- ❖ LUBRICATING OILS
- ❖ L.D.O & FURNACE OIL
- ❖ RUBBER PROCESS OILS
- ❖ BASE OILS
- ❖ PETROLEUM JELLY
- ❖ WAXES
- ❖ INDUSTRIAL SOLVENTS
- ❖ PLASTISIZERS
- ❖ ALL TYPES OF RAW RUBBER

COMMUNICATION ADDRESS :-

2/604 Trimurti Building, Next To Joggers Park, Siddharth Nagar, Vivek College Road, Goregaon West, Mumbai :- 400104, Maharashtra, India.

PHONE :- 7666981997 , 7777006911

TELEPHONE :- 7900006311

EMAIL ID :- info@rkpetroleums.com

WEBSITE :- www.rkpetroleums.com