



Where Quality Comes First



TURBINE OIL

CONTENTS:

ARKO TURBONOL 32	3-9
ARKO TURBONOL 46	10-16
ARKO TURBONOL 57	17-23
ARKO TURBONOL 68	24-30
ARKO TURBONOL T32	31-37
ARKO TURBONOL T46	38-44
ARKO TURBONOL T68	45-51

ARKO TURBONOL 32

Section 1: Identification of the Substance / N	I ixture			
1.1 Product identifier				
Product name	ARKO TURBONOL 32			
Product description	Turbine Oil			
Product type	Industrial Oil			
MARPOL Annex-1	****			
1.2 Identified uses				
Distribution of substance	Industrial			
Formulation & (re)packing of substance &	Industrial			
mixtures				
Manufacture of substance	Industrial			
Functional fluids	Industrial			
Section 2: Hazard Identification				
4-	Health	1		
Extrem	Flammability	1		
e3-	Reactivity	0		
High	Special			
2-Moderate				
1-Slight				
Section 3: Compostion / Information on Ingredients				
	CAGN NA PARAMETER AND A PARAME			
Product / Ingredient name		ture of hydro-treated hydrocarbons.		
Section 4: First Aid Measures				
Inhalation exposure	Remove to fresh air & prov	vide oxygen, if breathing is difficult. Contact physician		
Skin contact	Remove contaminated clot	hing. Flush skin with water. Wash skin thoroughly		
DAM COMME	with mild soap & water. If	irritation occurs, call a phys <mark>ician</mark> .		
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.			
Swanowing or other				
Eye contact	Rinse continuously with wairritation persists.	ater for several minutes. Get medical attention, if		
Protection first-aiders	Disconnecting electrical su	pply. Ensure adequate ventilation and check that a		
	safe and breathing area is a	vailable before entry into confined spaces.		
Section 5: Fire Fighting Measures				
5.1 Extinguishing media				
Unsuitable extinguishing media	* *	bon dioxide. Do not use direct water and wet		
		purning product. They may spread the fire. Use		
foam simultaneously on the surface. 5.2 Special hazards arising from the substance or mixture				
Hazards from the substance or mixture	Flammable liquids in press to heat, creating a highly f	surised containers may rupture and when exposed lammable vapour cloud.		
		likely to give rise to a complex mixture of airborne		
Hazardous thermal decomposition	<u> </u>	s, gases, including carbon monoxide, H_2S , SO_x		
products	(sulphur oxides) or sulphuric acid and unidentified organic and inorganic			
	compounds.			

5.3 Advice for firefighters	
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Noaction shall be taken involving any personal risk or without suitable training.
Special protective equipment for firefight	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
Section 6: Accidental Release Measures	
6.1 Personal precautions, protective equi	pment and emergency procedures
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly
	dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable for H ₂ S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable
6.3 Methods and material for containmen	mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.

~ 4 ~

Small spill

Stop leak if without risk. Absorb spilled product with suitable non-combustible

	materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do notuse water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds incase of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents. Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that havebeen opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.
7.3 Specific end use(s) – Recommendations	Not available
Section 8: Exposure Controls / Personal Pr	rotection
The list of Identified Uses in Section 1 sho Exposure Scenario(s).	ould be consulted for any available use-specific information provided in the
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name	Distillates, mixture of hydrocarbons
Exposure limits values	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume STEL: 3 mg/m³ 15 minutes. Form: mist and fume [Air contaminant]. AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume STEL: 3 mg/m³ 15 minutes. Form: mist and fume.
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents formethods for the determination of hazardous substances will also be

	required.
8.2 Exposure control Appropriate engineering controls	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the productand the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Properti	ies
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
рН	Not applicable
Pour point	<-15 °C (ASTM D 97)
Flash point	> 215 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max at 15 °C
Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available

		Saf	fetv Data-Sheet			
Decomposition temperatu	 ire	No data				
		>300 °C				
			32 cst @ (ASTM D 445) (Typical Value)			
•		No data	o i i i o i (i j piour i	, arac)		
		No data				
DMSO extractable compo	ounds for base oil	Not available	e			
substance(s) according to		<3 %				
Section 10: Stability and						
10.1 Reactivity		-	test data related to react	tivity available for this p	roduct or its	
10.2 Chemical stability		ingredients. Stable under	r normal conditions			
<u>_</u>	ibility of hazardous reactions Under		nder normal conditions of storage and use, hazardous reactions will not occur			
10.4 Conditions to avoid		Oxidising ag Keep away f	from extreme heat and	oxidising agents.		
10.5 Incompatible materi	als				nixture of	
10.6 Hazardous decompo	1.1 11.1 11.1 1 1 1 1 1 1 1 1 1 1 1 1 1			on monoxide,		
SECTION 11: Toxicologi						
11.1 Information on toxic	cological effects					
Acute toxicity		//	\			
Product / ingredient name	Resul	lt	Species	Dose	Exposure	
Distillate	LC 50 Inhalat		Rat	>2.18mg/l	4 hours	
(Petroleum), hydro treated heavy	LD 50 De	ermal	Rabbit	> 5000 mg/kg	<u> </u>	
paraffinic	LD 50 C	Oral	Rat	>15000 mg/kg	_	
Irritation / corrosion				mg/kg		
Skin						
Eye		No known si	ignificant effects or crit	tical hazards.		
Respiratory						
Sensation						
Skin						
Respiratory		No known si	ignificant effects or crit	rical hazards.		
		No data avai	ilable to indicate produ	ict or any components r	resent	
Mutagenicity		No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.				
Carcinogenicity		The base oil(s) in this product is based on an severely hydrotreated distillate.				
Reproductive toxicity		The product should not be regarded as a carcinogen. Contains no ingredient listed				
		as toxic to re	eproduction.			
Specific target organ toxic exposure	city – single	Not classifie	ed			
Specific target organ toxic exposure	ity – repeated					
Aspiration hazard		Aspiration hazard – Category 1				
Information on likely rout	es of exposure	Not available				
Potential acute health effec	ets					
Eye contact		Eye contact	may cause redness and	transient pain.		
Inhalation		Inhalation of	Inhalation of oil mist or vanours at elevated temperatures may cause respiratory			

Inhalation

Inhalation of oil mist or vapours at elevated temperatures may cause respiratory

	irrita	tion.			
Skin contact	No k	No known significant effects or critical hazards.			
Ingestion	May	be fatal if swallowed and er	nters airways.		
Potential chronic health effects					
General	No known significant effects or critical hazards.				
Carcinogenicity	 	pase oil(s) in this product is act should not beregarded a		drotreated distillate. The	
Mutagenicity					
	N.T. 1		22 11 1		
	No k	nown significant effects or o	critical nazards.		
Teratogenicity					
Product / ingredient name					
Fertility effects					
Other information Specific h	nazard Not a	vailable			
Section 12: Ecological Informa					
12.1 Toxicity		expected to be harmful to ac	quatic organisms.		
12.2 Persistence and degradab		nherently biodegradable.			
12.3 Bioaccumulative potentia	l Bioa	ccumulation is unlikely to b	e significant because of	the low water solubility	
12.4 Makilitaria and	of this product.				
12.4 Mobility in soil 12.5 Results of PBT & vPvB as		Not considered mobile.			
	Tot applicable				
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.				
Section 13: Disposal Consider	ations				
The information in this section consulted for any available use		<u> </u>		ection 1 should be	
Product Methods of disposal	used or in autho	re possible (e.g. in the abser- substance is feasible and re- cinerated, subject to national prisations, relevant contaminal lation. Contaminated or was	commended. This substa Il/local nation limits, safety regu	nce can be burned lations and air quality	
		can be carried out directly, or by delivery to qualified waste handlers. National			
		legislation may identify a specific organisation, and/or prescribe composition			
		limits and methods for recovery or disposal			
Hazardous waste		Yes			
European waste catalogue (E Code 13 03 07*	WC) Waste Wa	Waste designation.			
Packaging	Mi	Mineral-based non-chlorinated insulating and heat transmission oils.			
Methods of disposal	The generation of waste should be avoided or minimised wherever possi Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		-		
Section 14: Transport Informa					
International transport regula					
	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification	
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated	
14.2 UN proper shipping name	_	_	_	_	
14.3 Transport hazard	_	_	_	_	
class(es)					

No	No	No
_	_	_
	_	

14.6 Special precautions for user oils

14.7 Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

1501/2000 (REHOH)		
Annex XIV – List of substances subject to authorisation Annex XIV Substances of very high concern	None of the components are listed	
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable	
International Lists National Inventory	Inventory name	
Australia	Australian Inventory of Chemical Substances (AICS) – Yes	
Canada	Domestic Substances List (DSL) – Yes Non-Domestic Substances List (NDSL) – No	
China	Inventory of Existing Chemical Substances in China (IECSC) – Yes	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS) – Yes	
	European List of Notified Chemical Substances (ELINCS) – No	
Japan	Inventory of Existing and New Chemical Substances (ENCS) – Yes	
Korea	Existing Chemicals List (ECL) – Yes	
New Zealand	New Zealand Inventory – Yes	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes	
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory – Yes	

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16:	Other Information

Revision comments	
Legend to abbreviations	
ADR	European agreement concerning the international carriage of dangerous good
	by road.
RID	Regulations agreement concerning the international carriage of dangerous good
	by rail.
IMDG Code	International Maritime Dangerous Goods Code.
ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC)
	No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of

	Chemicals Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. R K PETROLEUMS makes no warranties expressed or implied in respect of the adequacyof this document for any particular purpose.

ARKO TURBONOL 46

Section 1: Identification of the Substance / Mixture			
1.1 Product identifier			
Product name	ARKO TURBONOL 46		
Product description	Turbine Oil		
Product type	Industrial Oil		
MARPOL Annex-1	****		
1.2 Identified uses			
Distribution of substance	Industrial		
Formulation & (re)packing of substance & mixtures	Industrial		
Manufacture of substance	Industrial		
Functional fluids	Industrial		
Section 2: Hazard Identification			
4-	Health 1		
Extrem	Flammability 1		
e3-	Reactivity 0		
High	Special		
2-Moderate			
1-Slight			
Section 3: Compostion / Information on Ingredients			
Product / Ingredient name	CAS No.: Not applicable for blended product. Distillates (Petroleum) mixture of hydro-treated hydrocarbons.		
Section 4: First Aid Measures			
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician		
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.		
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.		
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.		
Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.		
Section 5: Fire Fighting Measures			
5.1 Extinguishing media			
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use		

	foam simultaneously on the surface.		
5.2 Special hazards arising from the substance or mixture			
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.		
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid andunidentified organic and inorganic compounds.		
5.3 Advice for firefighters			
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Noaction shall be taken involving any personal risk or without suitable training.		
Special protective equipment for firefighte	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.		
Section 6: Accidental Release Measures			
6.1 Personal precautions, protective equip	ment and emergency procedures		
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.		
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons.		
	Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable for H ₂ S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.		

6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do notuse water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including anyincompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may
	contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.
7.3 Specific end use(s) – Recommendations	<u> </u>
Section 8: Exposure Controls / Personal Pr	
•	ould be consulted for any available use-specific information provided in the
Occupational exposure limits	
Product / Ingredient name	Distillates, mixture of hydrocarbons
Exposure limits values	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m ³ 8 hours. Form: mist and fume STEL: 3 mg/m ³ 15 minutes. Form: mist and fume [Air contaminant]. AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m ³ 8 hours. Form: mist and fume

	STEL: 3 mg/m³ 15 minutes. Form: mist and fume.
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance
	for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents
	formethods for the determination of hazardous substances will also be required.
8.2 Exposure control Appropriate engineering controls	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	photia de asea to avoia overneamig.
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handlingthis product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard it a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Proper	ties
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point The last of the las	<-12°C (ASTM D-97)
Flash point	> 215 °C

Evaporation rate	Not available		
Flammability (solid, gas)	Not available		
Flammability limits in air (lower), % by volume	Not available		
Flammability limits in air (upper), % by volume	Not available		
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)		
Density Solubility (ies)	0.88 max at 15 °C		
Solubility (water)	Insoluble in water		
Partition coefficient (n-octanol/water)	Not available		
Decomposition temperature	No data		
Auto-ignition temperature	>300 °C		
Kinematic viscosity at 40 °C (104 °F)	46 cst (ASTM D 445) (Typical Value)		
Explosive properties	No data		
Oxidising properties	No data		
DMSO extractable compounds for base oil	Not available		
substance(s) according to IP346	<3 %		
Section 10: Stability and Reactivity			
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	Stable under normal conditions		
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.		
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.		
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of		
10.6 Hazardous decomposition products	airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid and unidentified organic		
SECTION 11: Toxicological Information	and inorganic compounds.		

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient	Result	Species	Dose	Exposure
name				
Distillate	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
(Petroleum), hydro treated heavy	LD 50 Dermal	Rabbit	> 5000 mg/kg	
paraffinic	LD 50 Oral	Rat	>15000 mg/kg	_

Irritation / corrosion		
Skin		
Eye	No known significant effects or critical hazards.	
Respiratory		
Sensation		
Skin	No known significant effects or critical hazards.	
Respiratory	140 Known significant cricers of critical nazards.	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.	
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.	
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed	

	as toxic to reproduction.		
Specific target organ toxicity – single			
exposure	Not classified		
Specific target organ toxicity – repeated exposure			
Aspiration hazard	Aspiration hazard – Category 1		
Information on likely routes of exposure	Not available		
Potential acute health effects			
Eye contact	Eye contact may cause redness and transient pain.		
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.		
Skin contact	No known significant effects or critical hazards.		
Ingestion	May be fatal if swallowed and enters airways.		
Potential chronic health effects			
General	No known significant effects or critical hazards.		
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.		
Mutagenicity			
o ,			
	No known significant effects or critical hazards.		
Teratogenicity			
Product / ingredient name			
Fertility effects			
Other information Specific hazard	Not available		
Section 12: Ecological Information			
12.1 Toxicity	Not expected to be harmful to aquatic organisms.		
12.2 Persistence and degradability	Not inherently biodegradable.		
12.3 Bioaccumulative potential			
V	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.		
12.4 Mobility in soil	Not considered mobile.		
12.5 Results of PBT & vPvB assessment	& vPvB assessment Not applicable		
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.		
Section 13: Disposal Considerations			
	eneric advice and guidance. The list of Identified Uses in Section 1 should be formation provided in the Exposure Scenario(s).		
Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminatedor waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal		
Hazardous waste	Yes		
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.		
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.		
Methods of disposal	The generation of waste should be avoided or minimised wherever possible.		

	Waste packaging should berecycled. Incineration or landfill should only be			Ifill should only be	
considered when recycling is not feasible. Section 14: Transport Information					
International transport regulations					
7	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification	
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated	
14.2 UN proper shipping					
name					
14.3 Transport hazard class(es)	_	_	_	_	
14.4 Packing group	_	<u> </u>	_	_	
14.5 Environmental hazards	No	No	No	No	
Additional Information	_		_	_	
14.6 Special precautions for us	ser oils				
14.7 Transport in bulk accordi	ing to Annex I of MARP	OL 73/78 and the IBC C	Code		
Section 15: Regulatory Inform	ation				
15.1 Safety, health and environ 1907/2006 (REACH)	mental regulations / leg	islation specific for the s	ubstance or mixture EU	Regulation (EC) No.	
Annex XIV – List of substanct to authorisation Annex XIV Substances of very high concessions.	None of	the components are liste	ed		
Annex XVII – Restrictions of					
manufacture, placing on the r		cable			
use of certain dangerous subs					
mixtures and articles.					
International Lists National In	ve <mark>nto</mark> ry Inventory	y name			
Australia	Australian Inventory of Chemical Substances (AICS) – Yes		Yes		
Canada	Domestic Substances List (DSL) – Yes				
Canada	Non-Domestic Substances List (NDSL) – No				
China		Inventory of Existing Chemical Substances in China (IECSC) – Yes			
Europe					
	Europear	European List of Notified Chemical Substances (ELINCS) – No			
Japan	Inventor	Inventory of Existing and New Chemical Substances (ENCS) – Yes			
Korea		Existing Chemicals List (ECL) – Yes			
New Zealand	New Zea	New Zealand Inventory – Yes			
Philippines		Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes			
United States & Puerto Rico			TSCA) Inventory – Yes		
*A "Yes" indicates that all con					
				the inventory	
administered by the governing country(s).					
Section 16: Other Information	<u> </u>				
Revision comments					
Legend to abbreviations					
ADR	Europear by road.	n agreement concerning	g the international carria	age of dangerous good	
RID	Regulations agreement concerning the international carriage of dangerous by rail.		riage of dangerous good		
IMDG Code	Internati	onal Maritime Dangero	us Goods Code.		

ICAO	International Civil Aviation Organization.	
IATA	International Air Transport Association.	
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.	
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].	
SCBA	Self-Contained Breathing Apparatus.	
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].	
LC 50	Median lethal concentration.	
LD 50	Median lethal dose.	
PBT	Persistent, Bio accumulative and Toxic.	

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU)

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. R K PETROLEUMS makes no warranties expressed or implied in respect of the adequacyof this document for any particular purpose.

ARKO TURBONOL 57

Section 1: Identification of the Substance / M	Section 1: Identification of the Substance / Mixture		
1.1 Product identifier			
Product name	ARKO TURBONOL 57		
Product description	Turbine Oil		
Product type	Industrial Oil		
MARPOL Annex-1	****		
1.2 Identified uses			
Distribution of substance	Industrial		
Formulation & (re)packing of substance & mixtures	Industrial		
Manufacture of substance	Industrial		
Functional fluids	Industrial		
Section 2: Hazard Identification			
4-	Health	1	
Extrem	Flammability	1	
e3-	Reactivity	0	
High	Special	-	
2-Moderate			
1-Slight			
Section 3: Compostion / Information on Ing	redients		
Product / Ingredient name	CAS No.: Not applicable for blended product. Distillates (Petroleum) mixture of hydro-treated hydrocarbons.		
Section 4: First Aid Measures			
Inhalation exposure	Remove to fresh air & provi	de oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.		
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.		
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.		

Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.		
Section 5: Fire Fighting Measures			
5.1 Extinguishing media			
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.		
5.2 Special hazards arising from the substan	ce or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.		
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid andunidentified organic and inorganic compounds.		
5.3 Advice for firefighters			
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Noaction shall be taken involving any personal risk or without suitable training.		
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.		
Section 6: Accidental Release Measures	protection for elemical metacitis.		
6.1 Personal precautions, protective equipm	ant and amarganey procedures		
	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the		
For non-emergency personnel	emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of		
	product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current		
	direction and speed) may significantly influence the choice of appropriate		
	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken.		
For emergency responders	Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection: A half or full-face respirator with filter(s) for organic		
	vapours (and when applicable for H ₂ S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.		

6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanicalmeans. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do notuse water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including anyincompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty containers may
	contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.
7.3 Specific end use(s) – Recommendations	<u> </u>
Section 8: Exposure Controls / Personal Pr	
•	ould be consulted for any available use-specific information provided in the
Occupational exposure limits	
Product / Ingredient name	Distillates, mixture of hydrocarbons
Exposure limits values	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m ³ 8 hours. Form: mist and fume STEL: 3 mg/m ³ 15 minutes. Form: mist and fume [Air contaminant]. AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m ³ 8 hours. Form: mist and fume

	STEL: 3 mg/m³ 15 minutes. Form: mist and fume.
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European
	Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents formethods for the determination of hazardous substances will also be required.
8.2 Exposure control Appropriate engineering controls	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	should be used to avoid overheating.
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handlingthis product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the productand the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Proper	ties
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH Pove point	Not applicable
Pour point Flash point	<-12°C (ASTM D-97) > 215 °C
Flash point	Y 213 C

Evaporation rate	Not available	
Flammability (solid, gas)	Not available	
Flammability limits in air (lower), % by volume	Not available	
Flammability limits in air (upper), % by volume	Not available	
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)	
Density Solubility (ies)	0.88 max at 15 °C	
Solubility (water)	Insoluble in water	
Partition coefficient (n-octanol/water)	Not available	
Decomposition temperature	No data	
Auto-ignition temperature	>300 °C	
Kinematic viscosity at 40 °C (104 °F)	57 cst (ASTM D 445) (Typical Value)	
Explosive properties	No data	
Oxidising properties	No data	
DMSO extractable compounds for base oil	Not available	
substance(s) according to IP346	<3 %	
Section 10: Stability and Reactivity		
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	Stable under normal conditions	
10.3 Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions Oxidising agent.		
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.	
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of	
10.6 Hazardous decomposition products	airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid and unidentified organic	
SECTION 11: Toxicological Information	and inorganic compounds.	

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
(Petroleum), <mark>hydro</mark> treated heavy	LD 50 Dermal	Rabbit	> 5000 mg/kg	_
paraffinic	LD 50 Oral	Rat	>15000 mg/kg	_

Irritation / corrosion	
Skin Eye	No known significant effects or critical hazards.
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	140 Known significant effects of effical nazards.
Mutagenicity	No data available to indicate product or any components present greater than 0.1% are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed

	as toxic to reproduction.	
Specific target organ toxicity – single exposure	Not classified	
Specific target organ toxicity – repeated exposure		
Aspiration hazard	Aspiration hazard – Category 1	
Information on likely routes of exposure	Not available	
Potential acute health effects		
Eye contact	Eye contact may cause redness and transient pain.	
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.	
Skin contact	No known significant effects or critical hazards.	
Ingestion	May be fatal if swallowed and enters airways.	
Potential chronic health effects		
General	No known significant effects or critical hazards.	
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.	
Mutagenicity		
- Indiana in the second		
	No known significant effects or critical hazards.	
Teratogenicity		
Product / ingredient name		
Fertility effects		
Other information Specific hazard	Not available	
Section 12: Ecological Information		
12.1 Toxicity	Not expected to be harmful to aquatic organisms.	
12.2 Persistence and degradability	Not inherently biodegradable.	
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.	
12.4 Mobility in soil	Not considered mobile.	
12.5 Results of PBT & vPvB assessment	Not applicable	
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.	
Section 13: Disposal Considerations	buildings to organisms. Only gen transfer court also be impaired.	
The information in this section contains get	neric advice and guidance. The list of Identified Uses in Section 1 should be formation provided in the Exposure Scenario(s).	
Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminatedor waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal	
Hazardous waste	Yes	
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.	
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible.	
Tradiods of disposal	-	

Waste packaging should berecycled. Incineration or landfill should only be					
Section 14: Transport Informa	considered when recycling is not feasible. Section 14: Transport Information				
International transport regulations					
7	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification	
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated	
14.2 UN proper shipping	_	_	_	_	
name					
14.3 Transport hazard class(es)	_	_	_	_	
14.4 Packing group	_	A -	_	_	
14.5 Environmental hazards	No	No	No	No	
Additional Information	_		_	_	
14.6 Special precautions for us	ser oils				
14.7 Transport in bulk accordi	ing to Annex I of MARP	OL 73/78 and the IBC C	Code		
Section 15: Regulatory Inform					
15.1 Safety, health and environ 1907/2006 (REACH)	mental regulations / leg	islation specific for the s	substance or mixture EU	Regulation (EC) No.	
Annex XIV – List of substance to authorisation Annex XIV Substances of very high concessions.	None of	the components are liste	ed		
Annex XVII – Restrictions of					
manufacture, placing on the r		cable			
use of certain dangerous subs					
mixtures and articles.					
International Lists National In	ventory Inventory	y name			
Australia	Australia	n Inventory of Chemica	al Substances (AICS) –	Yes	
Canada	Domestic Substances List (DSL) – Yes				
Non-Domestic Substances List (NDSL) – No					
China	Inventor	Inventory of Existing Chemical Substances in China (IECSC) – Yes			
	Europear	European List of Notified Chemical Substances (ELINCS) – No			
Japan	Inventor	Inventory of Existing and New Chemical Substances (ENCS) – Yes			
Korea	Existing	Existing Chemicals List (ECL) – Yes			
New Zealand		New Zealand Inventory – Yes			
Philippines		Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes			
United States & Puerto Rico					
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)					
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).					
Section 16: Other Information					
Revision comments					
Legend to abbreviations					
ADR	European agreement concerning the international carriage of dangerous good by road.			nge of dangerous good	
RID	Regulations agreement concerning the international carriage of dangerous go by rail.		riage of dangerous good		
IMDG Code	Internation	International Maritime Dangerous Goods Code.			

ICAO	International Civil Aviation Organization.
IATA	International Air Transport Association.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].
SCBA	Self-Contained Breathing Apparatus.
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].
LC 50	Median lethal concentration.
LD 50	Median lethal dose.
PBT	Persistent, Bio accumulative and Toxic.

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. R K PETROLEUMS makes no warranties expressed or implied in respect of the adequacyof this document for any particular purpose.

ARKO TURBONOL 68

Section 1: Identification of the Substance / Mixture			
1.1 Product identifier			
Product name	ARKO TURBONOL 68		
Product description	Turbine Oil		
Product type	Industrial Oil		
MARPOL Annex-1	****		
1.2 Identified uses			
Distribution of substance	Industrial		
Formulation & (re)packing of substance & mixtures	Industrial		
Manufacture of substance	Industrial		
Functional fluids	Industrial		
Section 2: Hazard Identification			
4-	Health 1		
Extrem	Flammability 1		
e3-	Reactivity 0		
High	Special —		
2-Moderate			
1-Slight			
Section 3: Compostion / Information on Ing	redients		
Product / Ingredient name	CAS No.: Not applicable for blended product. Distillates (Petroleum) mixture of hydro-treated hydrocarbons.		
Section 4: First Aid Measures			
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician		
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.		
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.		
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.		

Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.
Section 5: Fire Fighting Measures	
5.1 Extinguishing media	
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.
5.2 Special hazards arising from the substan	ce or mixture
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.
5.3 Advice for firefighters	
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Noaction shall be taken involving any personal risk or without suitable training.
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
Section 6: Accidental Release Measures	protection for chemical incidents.
6.1 Personal precautions, protective equipm	cont and amanganay procedures
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly
	dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable for H ₂ S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanicalmeans. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do notuse water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on gene <mark>ral information – hygiene, storage</mark>	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents. Keep only in the original container or in a suitable container for this kind of
	product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that havebeen opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.
7.3 Specific end use(s) – Recommendations	
Section 8: Exposure Controls / Personal Pr	
•	uld be consulted for any available use-specific information provided in the
Occupational exposure limits	
Product / Ingredient name	Distillates mixture of hydrogerhons
Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume STEL: 3 mg/m³ 15 minutes. Form: mist and fume [Air contaminant]. AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume

	STEL: 3 mg/m ³ 15 minutes. Form: mist and fume.
Recommended monitoring procedure	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance
	for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents formethods for the determination of hazardous substances will also be required.
8.2 Exposure control Appropriate engineering controls	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the productand the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Prop	erties
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point Flash point	<-6°C (ASTM D-97)
Flash point	> 215 °C

Evaporation rate	Not available		
Flammability (solid, gas)	Not available		
Flammability limits in air (lower), % by volume	Not available		
Flammability limits in air (upper), % by volume	Not available		
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)		
Density Solubility (ies)	0.88 max at 15 °C		
Solubility (water)	Insoluble in water		
Partition coefficient (n-octanol/water)	Not available		
Decomposition temperature	No data		
Auto-ignition temperature	>300 °C		
Kinematic viscosity at 40 °C (104 °F)	68 cst (ASTM D 445) (Typical Value)		
Explosive properties	No data		
Oxidising properties	No data		
DMSO extractable compounds for base oil	Not available		
substance(s) according to IP346	<3 %		
Section 10: Stability and Reactivity			
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	Stable under normal conditions		
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.		
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.		
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of		
10.6 Hazardous decomposition products	airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid and unidentified organic		
SECTION 11: Toxicological Information	and inorganic compounds.		

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient	Result	Species	Dose	Exposure
name				
Distillate	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
(Petroleum), hydro treated heavy	LD 50 Dermal	Rabbit	> 5000 mg/kg	
paraffinic	LD 50 Oral	Rat	>15000 mg/kg	_

Irritation / corrosion	
Skin	
Eye	No known significant effects or critical hazards.
Respiratory	
Sensation	
Skin	No known significant effects or critical hazards.
Respiratory	100 known significant critects of critical hazards.
Mutagenicity	No data available to indicate product or any components present
	greater than 0.1 % are multigene or genotoxic.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.
Reproductive toxicity	The product should not be regarded as a
reproductive toxicity	carcinogen. Contains no ingredient listed

	as toxic to reproduction.		
Specific target organ toxicity – single			
exposure	Not classified		
Specific target organ toxicity – repeated exposure			
Aspiration hazard	Aspiration hazard – Category 1		
Information on likely routes of exposure	Not available		
Potential acute health effects			
Eye contact	Eye contact may cause redness and transient pain.		
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.		
Skin contact	No known significant effects or critical hazards.		
Ingestion	May be fatal if swallowed and enters airways.		
Potential chronic health effects			
General	No known significant effects or critical hazards.		
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.		
Mutagenicity			
ů ,			
	No known significant effects or critical hazards.		
Teratogenicity			
Product / ingredient name			
Fertility effects			
Other information Specific hazard	Not available		
Section 12: Ecological Information			
12.1 Toxicity	Not expected to be harmful to aquatic organisms.		
12.2 Persistence and degradability	Not inherently biodegradable.		
12.3 Bioaccumulative potential			
V	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.		
12.4 Mobility in soil	Not considered mobile.		
12.5 Results of PBT & vPvB assessment	Not applicable		
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.		
Section 13: Disposal Considerations			
	eneric advice and guidance. The list of Identified Uses in Section 1 should be formation provided in the Exposure Scenario(s).		
Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminatedor waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal		
Hazardous waste	Yes		
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.		
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.		
Methods of disposal	The generation of waste should be avoided or minimised wherever possible.		
Methods of disposal	The generation of waste should be avoided or minimised wherever possible.		

Waste packaging should berecycled. Incineration or landfill should only be considered when recycling is not feasible.					
Section 14: Transport Informa		ed when recycling is not	reasible.		
International transport regulations					
7	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification	
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated	
14.2 UN proper shipping	<u> </u>	—	_	_	
name					
14.3 Transport hazard class(es)	_	_	_	_	
14.4 Packing group	_		_	_	
14.5 Environmental hazards	No	No	No	No	
Additional Information	_		_	_	
14.6 Special precautions for us	ser oils				
14.7 Transport in bulk accordi	ing to Annex I of MARP	OL 73/78 and the IBC C	Code		
Section 15: Regulatory Inform					
15.1 Safety, health and environ 1907/2006 (REACH)	mental regulations / leg	islation specific for the s	substance or mixture EU	Regulation (EC) No.	
Annex XIV – List of substanct to authorisation Annex XIV Substances of very high concessions.	None of	the components are liste	ed		
Annex XVII – Restrictions of					
manufacture, placing on the r		cable			
use of certain dangerous subs					
mixtures and articles.					
International Lists National In	ventory Inventory	y name			
Australia	Australia	Australian Inventory of Chemical Substances (AICS) – Yes			
Canada	Domesti	Domestic Substances List (DSL) – Yes			
	Non-Dor	nestic Substances List	(NDSL) – No		
China	Inventor	y of Existing Chemical	Substances in China (II	ECSC) – Yes	
Europe	Europear – Yes	European Inventory of Existing Commercial Chemical Substances (EINECS)			
	Europear	List of Notified Chem	nical Substances (ELIN	CS) – No	
Japan	Inventor	y of Existing and New	Chemical Substances (I	ENCS) – Yes	
Korea	Existing	Chemicals List (ECL) -	– Yes		
New Zealand	New Zea	land Inventory – Yes			
Philippines	Philippin	e Inventory of Chemic	als and Chemical Subst	ances (PICCS) – Yes	
United States & Puerto Rico			TSCA) Inventory – Yes		
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory					
administered by the governing country(s).					
Section 16: Other Information					
Revision comments					
Legend to abbreviations					
ADR	Europear by road.	European agreement concerning the international carriage of dangerous good by road.			
RID	Regulatio by rail.	Regulations agreement concerning the international carriage of dangerous good by rail.			
IMDG Code	Internati	onal Maritime Dangero	ous Goods Code.		

ICAO	International Civil Aviation Organization.		
IATA	nternational Air Transport Association.		
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.		
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].		
SCBA	Self-Contained Breathing Apparatus.		
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].		
LC 50	Median lethal concentration.		
LD 50	Median lethal dose.		
PBT	Persistent, Bio accumulative and Toxic.		

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. R K PETROLEUMS makes no warranties expressed or implied in respect of the adequacyof this document for any particular purpose.

ARKO TURBONOL T32

Section 1: Identification of the Substance / N	Section 1: Identification of the Substance / Mixture			
1.1 Product identifier				
Product name	ARKO TURBONOL T32			
Product description	Turbine Oil			
Product type	Industrial Oil			
MARPOL Annex-1	****			
1.2 Identified uses				
Distribution of substance	Industrial			
Formulation & (re)packing of substance & mixtures	Industrial			
Manufacture of substance	Industrial			
Functional fluids	Industrial			
Section 2: Hazard Identification				
4-	Health 1			
Extrem	Flammability 1			
e3-	Reactivity 0			
High	Special —			
2-Moderate				
1-Slight				
Section 3: Compostion / Information on Ingredients				
Product / Ingredient name	CAS No.: Not applicable for blended product. Distillates (Petroleum) mixture of hydro-treated hydrocarbons.			
Section 4: First Aid Measures				
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician			
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.			
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.			
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.			

Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.	
Section 5: Fire Fighting Measures		
5.1 Extinguishing media		
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.	
5.2 Special hazards arising from the substan	ce or mixture	
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.	
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid andunidentified organic and inorganic compounds.	
5.3 Advice for firefighters		
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Noaction shall be taken involving any personal risk or without suitable training.	
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	
Section 6: Accidental Release Measures	protection for chemical incidents.	
6.1 Personal precautions, protective equipm	ont and amanganay proceedings	
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly	
	dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.	
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable for H ₂ S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.	

6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment	and cleaning up
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do notuse water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including any incompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds incase of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising agents.
	Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that havebeen opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do
	not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.
7.3 Specific end use(s) – Recommendations	Not available
Section 8: Exposure Controls / Personal Pro	1
•	ald be consulted for any available use-specific information provided in the
Occupational exposure limits	
Product / Ingredient name	Distillates, mixture of hydrocarbons
Exposure limits values	AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume STEL: 3 mg/m³ 15 minutes. Form: mist and fume [Air contaminant]. AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume

	STEL: 3 mg/m³ 15 minutes. Form: mist and fume.
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents formethods for the determination of hazardous substances will also be
	required.
8.2 Exposure control Appropriate engineering controls	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	product of diseases of our part of our par
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on thetask being performed and the risks involved and should be approved by a specialist before handlingthis product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard is a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Proper	
Appearance	Clear
Physical state	Liquid
Colour	Yellow
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	<-12°C (ASTM D-97)
Flash point	> 210 °C

Evaporation rate	Not available		
Flammability (solid, gas)	Not available		
Flammability limits in air (lower), % by volume	Not available		
Flammability limits in air (upper), % by volume	Not available		
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)		
Density Solubility (ies)	0.88 max at 15 °C		
Solubility (water)	Insoluble in water		
Partition coefficient (n-octanol/water)	Not available		
Decomposition temperature	No data		
Auto-ignition temperature	>300 °C		
Kinematic viscosity at 40 °C (104 °F)	31 cst @40 °C (ASTM D 445) (Typical Value)		
Explosive properties	No data		
Oxidising properties	No data		
DMSO extractable compounds for base oil	Not available		
substance(s) according to IP346	<3 %		
Section 10: Stability and Reactivity			
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	Stable under normal conditions		
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.		
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.		
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of		
10.6 Hazardous decomposition products	airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid and unidentified organic		
SECTION 11: Toxicological Information	and inorganic compounds.		

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient	Result	Species	Dose	Exposure
name				
	LC 50 Inhalation dusts	Rat	>2.18mg/l	4 hours
Distillate	and mists			
(Petroleum), hydro	LD 50 Dermal	Rabbit	> 5000	_
treated heavy			mg/kg	
paraffinic	LD 50 Oral	Rat	>15000	_
			mg/kg	

Irritation / corrosion		
Skin Eye	No known significant effects or critical hazards.	
Respiratory		
Sensation		
Skin	No known significant effects or critical hazards.	
Respiratory		
Mutagenicity	No data available to indicate product or any components present greater than 0.1% are multigene or genotoxic.	
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.	
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed	

	as toxic to reproduction.
Specific target organ toxicity – single exposure	Not classified
Specific target organ toxicity – repeated exposure	
Aspiration hazard	Aspiration hazard – Category 1
Information on likely routes of exposure	Not available
Potential acute health effects	
Eye contact	Eye contact may cause redness and transient pain.
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Skin contact	No known significant effects or critical hazards.
Ingestion	May be fatal if swallowed and enters airways.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.
Mutagenicity	
	No known significant effects or critical hazards.
Teratogenicity	
Product / ingredient name	
Fertility effects	
Other information Specific hazard	Not available
Section 12: Ecological Information	
12.1 Toxicity	Not expected to be harmful to aquatic organisms.
12.2 Persistence and degradability	Not inherently biodegradable.
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility
1210 Divinceumum ve potential	of this product.
12.4 Mobility in soil	Not considered mobile.
12.5 Results of PBT & vPvB assessment	Not applicable
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical
	damage to organisms. Oxygen transfer could also be impaired.
Section 13: Disposal Considerations	
	neric advice and guidance. The list of Identified Uses in Section 1 should be ormation provided in the Exposure Scenario(s).
Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminated or waste substance (not directly recyclable): Disposal
	can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal
Hazardous waste	Yes
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.
Methods of disposal	The generation of waste should be avoided or minimised wherever possible.

Waste packaging should be recycled. Incineration or landfill should only be					
considered when recycling is not feasible. Section 14: Transport Information					
International transport regulations					
Ţ	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification	
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated	
14.2 UN proper shipping					
name					
14.3 Transport hazard class(es)	_	_	_	_	
14.4 Packing group	_	<u> </u>	_	_	
14.5 Environmental hazards	No	No	No	No	
Additional Information	_		_	_	
14.6 Special precautions for us	ser oils				
14.7 Transport in bulk accordi	ing to Annex I of MARP	OL 73/78 and the IBC C	Code		
Section 15: Regulatory Inform	ation				
15.1 Safety, health and environ 1907/2006 (REACH)	mental regulations / leg	islation specific for the s	ubstance or mixture EU	Regulation (EC) No.	
Annex XIV – List of substanct to authorisation Annex XIV Substances of very high concessions.	None of	the components are liste	ed		
Annex XVII – Restrictions of					
manufacture, placing on the r		cable			
use of certain dangerous subs					
mixtures and articles.					
International Lists National In	ve <mark>nto</mark> ry Inventory	y name			
Australia	Australia	n Inventory of Chemica	al Substances (AICS) –	Yes	
Canada	Domestic Substances List (DSL) – Yes				
Canada Non-Domestic Substances List (NDSL) – No					
China		Inventory of Existing Chemical Substances in China (IECSC) – Yes			
Europe					
	Europear	List of Notified Chem	nical Substances (ELIN	CS) – No	
Japan	Inventor	Inventory of Existing and New Chemical Substances (ENCS) – Yes			
Korea		Existing Chemicals List (ECL) – Yes			
New Zealand	New Zea	New Zealand Inventory – Yes			
Philippines		Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes			
United States & Puerto Rico			TSCA) Inventory – Yes		
*A "Yes" indicates that all con					
governing country(s) A "No" indicates that one or m		product are not listed or	exempt from listing on	the inventory	
administered by the governing country(s).					
Section 16: Other Information					
Revision comments					
Legend to abbreviations					
ADR	European agreement concerning the international carriage of dangerous good by road.				
RID	Regulations agreement concerning the international carriage of dangerous goo by rail.			riage of dangerous good	
IMDG Code	Internati	International Maritime Dangerous Goods Code.			

ICAO	International Civil Aviation Organization.	
IATA	International Air Transport Association.	
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.	
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].	
SCBA	Self-Contained Breathing Apparatus.	
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].	
LC 50	Median lethal concentration.	
LD 50	Median lethal dose.	
PBT	Persistent, Bio accumulative and Toxic.	

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. R K PETROLEUMS makes no warranties expressed or implied in respect of the adequacyof this document for any particular purpose.

ARKO TURBONOL T46

Section 1: Identification of the Substance / Mixture		
1.1 Product identifier		
Product name	ARKO TURBONOL T46	
Product description	Turbine Oil	
Product type	Industrial Oil	
MARPOL Annex-1	****	
1.2 Identified uses		
Distribution of substance	Industrial	
Formulation & (re)packing of substance & mixtures	Industrial	
Manufacture of substance	Industrial	
Functional fluids	Industrial	
Section 2: Hazard Identification		
4-	Health 1	
Extrem	Flammability 1	
e3-	Reactivity 0	
High	Special —	
2-Moderate		
1-Slight		
Section 3: Compostion / Information on Ingredients		
Product / Ingredient name	CAS No.: Not applicable for blended product. Distillates (Petroleum) mixture of hydro-treated hydrocarbons.	
Section 4: First Aid Measures		
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician	
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.	
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.	
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.	
	~ 20 ~	

Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.		
Section 5: Fire Fighting Measures			
5.1 Extinguishing media			
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.		
5.2 Special hazards arising from the substan	ce or mixture		
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.		
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid andunidentified organic and inorganic compounds.		
5.3 Advice for firefighters			
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Noaction shall be taken involving any personal risk or without suitable training.		
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.		
Section 6: Accidental Release Measures	protection for chemical incidents.		
6.1 Personal precautions, protective equipm	ont and amoreonay procedures		
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly		
	dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.		
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable for H ₂ S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.		

6.2 Environmental precautions	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible materials. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities.
6.3 Methods and material for containment	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do notuse water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.
Section 7: Handling and Storage	
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.
7.2 Conditions for safe storage including anyincompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds incase of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising
	Agents. Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that havebeen opened must be carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do
	not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.
7.3 Specific end use(s) – Recommendations	Not available
Section 8: Exposure Controls / Personal Pr	
The list of Identified Uses in Section 1 sho Exposure Scenario(s).	uld be consulted for any available use-specific information provided in the
8.1 Control parameters	
Occupational exposure limits	
Product / Ingredient name Exposure limits values	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume STEL: 3 mg/m³ 15 minutes. Form: mist and fume [Air contaminant]. AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume

	STEL: 3 mg/m³ 15 minutes. Form: mist and fume.
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European
	Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents formethods for the determination of hazardous substances will also be required.
8.2 Exposure control Appropriate engineering controls	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.
Individual protection measures	briodia de asea to avora overneating.
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.
Eye / face protection	Recommended: Safety glasses with side shields.
Skin protection	
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on thetask being performed and the risks involved and should be approved by a specialist before handlingthis product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the productand the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Section 9: Physical and Chemical Propert	iies
Appearance	Clear
Physical state	Liquid
Colour	Water White
Odor	Petroleum odor
Odour threshold	Not available
pH	Not applicable
Pour point	<-18°C (ASTM D-97)
Flash point	> 210 °C

Evaporation rate	Not available
Flammability (solid, gas)	Not available
Flammability limits in air (lower), % by volume	Not available
Flammability limits in air (upper), % by volume	Not available
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Density Solubility (ies)	0.88 max at 15 °C
Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available
Decomposition temperature	No data
Auto-ignition temperature	>300 °C
Kinematic viscosity at 40 °C (104 °F)	47 cst (ASTM D 445) (Typical Value)
Explosive properties	No data
Oxidising properties	No data
DMSO extractable compounds for base oil	Not available
substance(s) according to IP346	<3 %
Section 10: Stability and Reactivity	
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of
10.6 Hazardous decomposition products	airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid and unidentified organic
SECTION 11: Toxicological Information	and inorganic compounds.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient	Result	Species	Dose	Exposure
name				
	LC 50 Inhalation dusts	Rat	>2.18mg/l	4 hours
Distillate	and mists		/ /	
(Petroleum), hydro	LD 50 Dermal	Rabbit	> 5000	_
treated heavy			mg/kg	
paraffinic	LD 50 Oral	Rat	>15000	_
			mg/kg	

Irritation / corrosion		
Skin		
Eye	No known significant effects or critical hazards.	
Respiratory		
Sensation		
Skin	No known significant effects or critical hazards.	
Respiratory	No known significant criects of critical nazards.	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.	
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.	
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed	

	as toxic to reproduction.	
Specific target organ toxicity – single		
exposure	Not classified	
Specific target organ toxicity – repeated		
exposure		
Aspiration hazard	Aspiration hazard – Category 1	
Information on likely routes of exposure	Not available	
Potential acute health effects		
Eye contact	Eye contact may cause redness and transient pain.	
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.	
Skin contact	No known significant effects or critical hazards.	
Ingestion	May be fatal if swallowed and enters airways.	
Potential chronic health effects		
General	No known significant effects or critical hazards.	
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not beregarded as a carcinogen.	
Mutagenicity		
	No known significant effects or critical hazards.	
Teratogenicity		
Product / ingredient name		
Fertility effects		
	Not available	
Other information Specific hazard	The manual state of the state o	
Section 12: Ecological Information		
12.1 Toxicity	Not expected to be harmful to aquatic organisms.	
12.2 Persistence and degradability	Not inherently biodegradable.	
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.	
12.4 Mobility in soil Not considered mobile.		
12.5 Results of PBT & vPvB assessment	Not applicable	
12.6 Other adverse effects	Insoluble in water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.	
Section 13: Disposal Considerations	1	
The information in this section contains ge	neric advice and guidance. The list of Identified Uses in Section 1 should be formation provided in the Exposure Scenario(s).	
Product Methods of disposal	Where possible (e.g. in the absence of relevant contamination), recycling of used substance is feasible and recommended. This substance can be burned or incinerated, subject to national/local authorisations, relevant contamination limits, safety regulations and air quality legislation. Contaminatedor waste substance (not directly recyclable): Disposal can be carried out directly, or by delivery to qualified waste handlers. National legislation may identify a specific organisation, and/or prescribe composition limits and methods for recovery or disposal	
Hazardous waste	Yes	
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.	
dackaging Mineral-based non-chlorinated insulating and heat transmission oils.		
Methods of disposal	The generation of waste should be avoided or minimised wherever possible.	

Waste packaging should be recycled. Incineration or landfill should only be					
Section 14: Transport Informa	considered when recycling is not feasible. Section 14: Transport Information				
International transport regulations					
Ţ	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification	
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated	
14.2 UN proper shipping	_	_	_	_	
name					
14.3 Transport hazard class(es)	_	_	_	_	
14.4 Packing group	_	<u> </u>	_	_	
14.5 Environmental hazards	No	No	No	No	
Additional Information	_		_	_	
14.6 Special precautions for us	ser oils				
14.7 Transport in bulk accordi	ing to Annex I of MARP	OL 73/78 and the IBC C	Code		
Section 15: Regulatory Inform					
15.1 Safety, health and environ 1907/2006 (REACH)	mental regulations / leg	islation specific for the s	substance or mixture EU	Regulation (EC) No.	
Annex XIV – List of substance to authorisation Annex XIV Substances of very high concessions.	None of	the components are liste	ed		
Annex XVII – Restrictions of					
manufacture, placing on the r		cable			
use of certain dangerous subs					
mixtures and articles.					
International Lists National In	ventory Inventory	y name			
Australia	Australia	n Inventory of Chemica	al Substances (AICS) –	Yes	
Canada	Domestic Substances List (DSL) – Yes				
Non-Domestic Substances List (NDSL) – No					
China	Inventor	Inventory of Existing Chemical Substances in China (IECSC) – Yes			
Europe				Substances (EINECS)	
	Europear	European List of Notified Chemical Substances (ELINCS) – No			
Japan	Inventor	Inventory of Existing and New Chemical Substances (ENCS) – Yes			
Korea	Existing	Existing Chemicals List (ECL) – Yes			
New Zealand		New Zealand Inventory – Yes			
Philippines		Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes			
United States & Puerto Rico					
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)					
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).					
Section 16: Other Information					
Revision comments					
Legend to abbreviations					
ADR	European agreement concerning the international carriage of dangerous goo by road.			nge of dangerous good	
RID	Regulations agreement concerning the international carriage of dangerous goo by rail.				
IMDG Code	Internation	International Maritime Dangerous Goods Code.			

ICAO	International Civil Aviation Organization.	
IATA	International Air Transport Association.	
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.	
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].	
SCBA	Self-Contained Breathing Apparatus.	
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].	
LC 50 Median lethal concentration.		
LD 50 Median lethal dose.		
PBT	Persistent, Bio accumulative and Toxic.	

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. R K PETROLEUMS makes no warranties expressed or implied in respect of the adequacyof this document for any particular purpose.

ARKO TURBONOL T68

Section 1: Identification of the Substance / Mixture			
1.1 Product identifier			
Product name	ARKO TURBONOL T68		
Product description	Turbine Oil		
Product type	Industrial Oil		
MARPOL Annex-1	****		
1.2 Identified uses			
Distribution of substance	Industrial		
Formulation & (re)packing of substance & mixtures	Industrial		
Manufacture of substance	Industrial		
Functional fluids	Industrial		
Section 2: Hazard Identification			
4-	Health 1		
Extrem	Flammability 1		
e3-	Reactivity 0		
High	Special —		
2-Moderate			
1-Slight			
Section 3: Compostion / Information on Ingredients			
Product / Ingredient name	CAS No.: Not applicable for blended product. Distillates (Petroleum) mixture of hydro-treated hydrocarbons.		
Section 4: First Aid Measures			
Inhalation exposure	Remove to fresh air & provide oxygen, if breathing is difficult. Contact physician		
Skin contact	Remove contaminated clothing. Flush skin with water. Wash skin thoroughly with mild soap & water. If irritation occurs, call a physician.		
Swallowing or other	Do not induce vomiting. In general no treatment is necessary unless large quantities are ingested. Get medical advice.		
Eye contact	Rinse continuously with water for several minutes. Get medical attention, if irritation persists.		
	~ 45 ~		

Protection first-aiders	Disconnecting electrical supply. Ensure adequate ventilation and check that a safe and breathing area is available before entry into confined spaces.
Section 5: Fire Fighting Measures	
5.1 Extinguishing media	
Unsuitable extinguishing media	Use dry powder, foam, carbon dioxide. Do not use direct water and wet chemicals, or water on the burning product. They may spread the fire. Use foam simultaneously on the surface.
5.2 Special hazards arising from the substan	nce or mixture
Hazards from the substance or mixture	Flammable liquids in pressurised containers may rupture and when exposed to heat, creating a highly flammable vapour cloud.
Hazardous thermal decomposition products	Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid andunidentified organic and inorganic compounds.
5.3 Advice for firefighters	
Special precautions for firefighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Noaction shall be taken involving any personal risk or without suitable training.
Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face- piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
Section 6: Accidental Release Measures	protection for enemiest increasing.
6.1 Personal precautions, protective equipm	nent and emergency procedures
For non-emergency personnel	Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay
	upwind / keep distance from source. In case of large spillages, alert occupants in downwind areas. Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations. Note: Recommended measures are based on the most likely spillage scenarios
	for this material; however, local conditions (wind, air temperature, wave / current direction and speed) may significantly influence the choice of appropriate actions.
For emergency responders	For this reason, local experts should be consulted when necessary. Local regulations may also prescribe or limit actions to be taken. Small spillages: Normal antistatic working clothes are usually adequate. Large spillages: Full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons.
	Note: Gloves made of PVA are not water-resistant, and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and / or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory Protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable for H ₂ S) a Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

	Prevent product from entering sewers, rivers or other bodies of water. If necessary dike the product with dry earth, sand or similar non-combustible	
6.2 Environmental precautions	materials. In case of soil contamination, remove contaminated soil and treat in	
OL ZIIVII OMMONIAI PI COMMONIS	accordance with local regulations. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents.	
	If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and,	
(2 M-41-1141	if required, approved by local authorities.	
6.3 Methods and material for containment	<u> </u>	
Small spill	Stop leak if without risk. Absorb spilled product with suitable non-combustible materials.	
Large spill	Large spillages may be cautiously covered with foam, if available, to limit vapour cloud formation. Do notuse water jet. When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.	
6.4 Reference to other sections	See Section 1: For emergency contact information. See Section 8: For information on appropriate personal protective equipment. See Section 13: For additional waste treatment information.	
Section 7: Handling and Storage		
7.1 Advice on general information – hygiene, storage	Obtain special instructions before use. Keep away from heat / sparks / open flames/hot surfaces. No smoking. Use and store only outdoors or in a well-ventilated area. Hazard of slipping on spilt product. Avoid release to the environment.	
7.2 Conditions for safe storage including anyincompatibilities	Storage area layout, tank design, equipment and operating procedures must comply with the relevant regional, national or local legislation. Storage installations should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations. Store separately from oxidising	
	agents. Keep only in the original container or in a suitable container for this kind of product. Keep container tightly closed and sealed until ready for use. Do not store in unlabelled containers. Containers that have	
	carefully resealed and kept upright to prevent leakage. Empty containers may contain harmful, flammable / combustible or explosive residue or vapours. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards. Protect from sunlight.	
7.3 Specific end use(s) – Recommendations	<u> </u>	
Section 8: Exposure Controls / Personal Pr		
The list of Identified Uses in Section 1 sho Exposure Scenario(s).	ould be consulted for any available use-specific information provided in the	
8.1 Control parameters		
Occupational exposure limits		
Product / Ingredient name	Distillates, mixture of hydrocarbons AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume	
Exposure limits values	STEL: 3 mg/m³ 15 minutes. Form: mist and fume [Air contaminant]. AFS 2015:7 (Sweden, 12/2015). TWA: 1 mg/m³ 8 hours. Form: mist and fume	

	STEL: 3 mg/m³ 15 minutes. Form: mist and fume.		
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance		
	for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents formethods for the determination of hazardous substances will also be required.		
8.2 Exposure control Appropriate engineering controls	Mechanical ventilation and local exhaust will reduce exposure via the air. Use oil resistant material in construction of handling equipment. Store under recommended conditions and if heated, temperature control equipment should be used to avoid overheating.		
Individual protection measures			
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. Wash contaminated clothing before reuse.		
Eye / face protection	Recommended: Safety glasses with side shields.		
Skin protection			
Hand protection	4 – 8 hours (breakthrough time): nitrile rubber.		
Body protection	Wear protective clothing if there is a risk of skin contact. Change contaminated clothes at the end of working shift.		
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handlingthis product.		
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the productand the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.		
Environmental exposure control	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Section 9: Physical and Chemical Prope	rties		
Appearance	Clear		
Physical state	Liquid		
Colour	Water White		
Odor	Petroleum odor		
Odour threshold	Not available		
pH	Not applicable		
Pour point Floring point	<-9°C (ASTM D-97)		
Flash point	> 220 °C		

Evaporation rate	Not available		
Flammability (solid, gas)	Not available		
Flammability limits in air (lower), % by volume	Not available		
Flammability limits in air (upper), % by volume	Not available		
Vapour pressure	≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)		
Density Solubility (ies)	0.88 max at 15 °C		
Solubility (water)	Insoluble in water		
Partition coefficient (n-octanol/water)	Not available		
Decomposition temperature	No data		
Auto-ignition temperature	>300 °C		
Kinematic viscosity at 40 °C (104 °F)	67 cst (ASTM D 445) (Typical Value)		
Explosive properties	No data		
Oxidising properties	No data		
DMSO extractable compounds for base oil	Not available		
substance(s) according to IP346	<3 %		
Section 10: Stability and Reactivity			
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	Stable under normal conditions		
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Oxidising agent.		
10.4 Conditions to avoid	Keep away from extreme heat and oxidising agents.		
10.5 Incompatible materials	Incomplete combustion is likely to give rise to a complex mixture of		
10.6 Hazardous decomposition products	airborne solid and liquid particulates, gases, including carbon monoxide, H ₂ S, SO _x (sulphur oxides) or sulphuric acid and unidentified organic and inorganic compounds.		
SECTION 11: Toxicological Information	and morganic compounds.		

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Distillate	LC 50 Inhalation dusts and mists	Rat	>2.18mg/l	4 hours
(Petroleum), hydro treated heavy	LD 50 Dermal	Rabbit	> 5000 mg/kg	
paraffinic	LD 50 Oral	Rat	>15000 mg/kg	_

п	. • 4		corrosion
п	rrita	non /	COPPOSION

Skin		
Eye	No known significant effects or critical hazards.	
Respiratory		
Sensation		
Skin	No known significant effects or critical hazards.	
Respiratory	100 known significant cricets of critical nazards.	
Mutagenicity	No data available to indicate product or any components present greater than 0.1 % are multigene or genotoxic.	
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate.	
Reproductive toxicity	The product should not be regarded as a carcinogen. Contains no ingredient listed	

	as toxic to reproduction.	
Specific target organ toxicity – single		
exposure	Not classified	
Specific target organ toxicity – repeated		
exposure		
Aspiration hazard	Aspiration hazard – Category 1	
Information on likely routes of exposure	Not available	
Potential acute health effects		
Eye contact	Eye contact may cause redness and transient pain.	
Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.	
Skin contact	No known significant effects or critical hazards.	
Ingestion	May be fatal if swallowed and enters airways.	
Potential chronic health effects		
General	No known significant effects or critical hazards.	
Carcinogenicity	The base oil(s) in this product is based on an severely hydrotreated distillate. The product should not be regarded as a carcinogen.	
Mutagenicity		
- Indiana in the second of the		
	No known significant effects or critical hazards.	
Teratogenicity		
Product / ingredient name		
Fertility effects		
Other information Specific hazard	Not available	
Section 12: Ecological Information		
12.1 Toxicity	Not expected to be harmful to aquatic organisms.	
12.2 Persistence and degradability Not inherently biodegradable.		
12.3 Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility	
	of this product.	
12.4 Mobility in soil	Not considered mobile.	
12.5 Results of PBT & vPvB assessment	Not applicable	
	Insoluble in water. Spills may form a film on water surfaces causing physical	
12.6 Other adverse effects	damage to organisms. Oxygen transfer could also be impaired.	
Section 13: Disposal Considerations		
	peric advice and guidance. The list of Identified Uses in Section 1 should be permation provided in the Exposure Scenario(s).	
	Where possible (e.g. in the absence of relevant contamination), recycling of	
	used substance is feasible and recommended. This substance can be burned	
Product Methods of disposal	or incinerated, subject to national/local	
	authorisations, relevant contamination limits, safety regulations and air quality	
	legislation. Contaminatedor waste substance (not directly recyclable): Disposal	
	can be carried out directly, or by delivery to qualified waste handlers. National	
	legislation may identify a specific organisation, and/or prescribe composition	
	limits and methods for recovery or disposal	
Hazardous waste	Yes	
European waste catalogue (EWC) Waste Code 13 03 07*	Waste designation.	
Packaging	Mineral-based non-chlorinated insulating and heat transmission oils.	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible.	

~ 50 ~

	-	ckaging should be recycling is not	cled. Incineration or land	Ifill should only be	
Section 14: Transport Informa		d when recycling is not	icasioic.		
International transport regular					
,	ADR / RID	ADN	IMO / IMDG Classification	ICAO / IATA Classification	
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated	
14.2 UN proper shipping name					
14.3 Transport hazard class(es)	_	_	_	_	
14.4 Packing group	_	A -	_	_	
14.5 Environmental hazards	No	No	No	No	
Additional Information	_		_	_	
14.6 Special precautions for us	er oils				
14.7 Transport in bulk accordi		OL 73/78 and the IBC C	Code		
Section 15: Regulatory Inform		1			
15.1 Safety, health and environ 1907/2006 (REACH)	mental regulations / leg	islation specific for the s	substance or mixture EU	Regulation (EC) No.	
Annex XIV – List of substance					
to authorisation Annex XIV		the components are liste	ed		
Substances of very high conc					
Annex XVII – Restrictions or		11			
manufacture, placing on the n		cable			
use of certain dangerous subst	tances,				
mixtures and articles.	rontour. Inventour	, nama			
International Lists National In			-1 C-1 (A ICC)	77	
			al Substances (AICS) –	res	
Canada		e Substances List (DSL nestic Substances List			
China		Inventory of Existing Chemical Substances in China (IECSC) – Yes			
Europe		European Inventory of Existing Commercial Chemical Substances (EINECS)			
	Europear	European List of Notified Chemical Substances (ELINCS) – No			
Japan	-	Inventory of Existing and New Chemical Substances (ENCS) – Yes			
Korea		Existing Chemicals List (ECL) – Yes			
New Zealand		New Zealand Inventory – Yes			
Philippines					
		Philippine Inventory of Chemicals and Chemical Substances (PICCS) – Yes			
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)					
	A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).				
Section 16: Other Informatio					
Revision comments					
Legend to abbreviations					
ADR		European agreement concerning the international carriage of dangerous good by road.			
RID	Regulat by rail.	Regulations agreement concerning the international carriage of dangerous goo by rail.			
IMDG Code	Internat	ional Maritime Danger	ous Goods Code.		

ICAO	International Civil Aviation Organization.	
IATA	International Air Transport Association.	
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.	
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008].	
SCBA	Self-Contained Breathing Apparatus.	
REACH	Registration, Evaluation, Authorization and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006].	
LC 50	Median lethal concentration.	
LD 50	Median lethal dose.	
PBT	Persistent, Bio accumulative and Toxic.	

Regulation (EC) no 1907/2006, Annex II as Amended by Commission Regulation (EU) 2015/830

Disclaimer: Information contained in this material data sheet is believed to be reliable, but no representation, guarantee or warranties of any kind made as to its accuracy, suitability for a particular application or results to be obtained from them. It is up to the manufacturer / seller to ensure that the information content in the material data sheet is relevant to the product manufactured / handled or sold by, as the case may be. R K PETROLEUMS makes no warranties expressed or implied in respect of the adequacyof this document for any particular purpose.







Where Quality Comes First

MANUFACTURERS OF:-

- ***** HYDRAULIC OILS
- ***** CUTTING OILS
- * MACHINE OILS

- **SILICONE EMULSION**
- **GREASES**
- **GEAR OILS**

TRADERS & MARKETERS OF:-

- **UBRICATING OILS**
- ❖ L.D.O & FURNACE OIL
- * RUBBER PROCESS OILS
- ***** BASE OILS

- **❖** PETROLEUM JELLY
- ***** WAXES
- *** INDUSTRIAL SOLVENTS**
- **❖** PLASTISIZERS
- ❖ ALL TYPES OF RAW RUBBER

COMMUNICATION ADDRESS:-

2/604 Trimurti Building, Next To Joggers Park, Siddharth Nagar, Vivek College Road, Goregaon West,

Mumbai :- 400104, Maharashtra, India.

PHONE :- 7666981997 I 7777006911

TELEPHONE :- 7900006311

EMAIL ID :- info@rkpetroleums.com

WEBSITE :- www.rkpetroleums.com